

TECHNICAL DATA SHEET

Date of Issue 03/2026 | Rev. 00_03/2026

4220 Entry Level Utility Painter's Masking Tape



PRODUCT DESCRIPTION

4220 Entry Level is a universal masking tape designed for light indoor painting and decorative jobs. Made with a saturated crepe paper backing and natural rubber adhesive, it ensures good adhesion and clean removal from most common surfaces such as plaster, wood, and metal. Its balanced paper strength and adhesive formulation make it suitable for short painting cycles, touch-ups, and do-it-yourself applications. The FSC® certified paper guarantees an environmentally responsible choice for versatile everyday use.

FEATURES

- Natural rubber adhesive
- Clean removal after use
- Easy unwinding
- Good adhesion on standard surfaces
- Indoor removal time: 5 Days
- FSC® certified paper backing

MAIN APPLICATIONS

- Light indoor painting and decoration
- Touch-up and maintenance jobs
- DIY masking applications
- General-purpose use on plaster, wood, and metal
- Suitable for Spray Painting

CONSTRUCTION

	Adhesive	Backing		
Material	Natural rubber	Saturated crepe paper		
Colour	<input checked="" type="radio"/> Transparent	<input type="radio"/> White	<input checked="" type="radio"/> Sharp Yellow	<input type="radio"/> Honey

TECHNICAL DATA*

	Metric	Imperial Units	Test Method
Total weight	75 g/m ²	2.21 oz/yd ²	ISO 536
Total thickness	105 µm	4.1 mils	Internal
MD tensile strength	34 N/cm	19.4 lb/in	AFERA 5004/PSTC 131
MD elongation at break	8 %	8 %	AFERA 5004/PSTC 131
Adhesion to steel plate	1.2 N/cm	11 oz/in	AFERA 5001/PSTC 101

*Typical value

All technical data provided is based on laboratory testing and is believed to be accurate. End users are responsible for determining product suitability for their intended application.

Technical Information and Product Use

All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. Figures shown refer to average values only, based on tests carried out in conditioned laboratory and are not valid for specification. The company reserves the right to modify or change the products at any time without notice. The accuracy or completeness of such information is not guaranteed. The technical information, suggestions and other statements contained in this document have been compiled for your guidance and usage. ATLAS Tapes Group reminds the user of the products to make sure that the product is used as per the instructions and suggestions provided. It is the user's sole responsibility to determine the suitability of the product in actual application under specific conditions.

Storage and Shelf Life

Suggested storage in dry area away from direct sunlight temperature should range from 59°F / 15°C to 77°F / 25°C with max relative humidity of 50%. Tape and jumbo roll should be used respectively within 12 months and 6 months from date of shipment. ATLAS Tapes Group does not take responsibility for the defective material if it is not stored and used in accordance with the conditions listed above.