

## TECHNICAL DATA SHEET

Date of Issue 03/2026 | Rev. 00\_03/2026

# 4260 Essential Utility Painter's Masking Tape



### PRODUCT DESCRIPTION

4260 Essential is a universal masking tape for general indoor decoration and finishing jobs. Made with saturated crepe paper and natural rubber adhesive, it ensures strong adhesion and clean removal without residue on common surfaces such as walls, wood, and metal. Its higher paper weight and coating level provide better tensile strength and durability than basic tapes, making it suitable for longer painting cycles and more demanding decorative tasks.

FSC® certified paper supports environmentally friendly use.

### FEATURES

- Natural rubber adhesive
- Clean removal after use
- Strong adhesion on walls and wood
- Controlled unwind and smooth application
- Consistent results on multiple coats
- Indoor removal time: 5 Days
- FSC® certified paper backing

### MAIN APPLICATIONS

- Indoor painting and finishing
- Decorative masking on plaster, wood, and metal
- Medium-duration painting cycles
- Home renovation and maintenance
- Suitable for Spray Painting

### CONSTRUCTION

	Adhesive	Backing
Material	Natural rubber	Saturated crepe paper
Colour	<input checked="" type="radio"/> Transparent	<input type="radio"/> White <input checked="" type="radio"/> Sharp Yellow <input checked="" type="radio"/> Brown

### TECHNICAL DATA\*

	Metric	Imperial Units	Test Method
Total weight	80 g/m <sup>2</sup>	2.36 oz/yd <sup>2</sup>	ISO 536
Total thickness	110 µm	4.3 mils	Internal
MD tensile strength	34 N/cm	19.4 lb/in	AFERA 5004/PSTC 131
MD elongation at break	8 %	8 %	AFERA 5004/PSTC 131
Adhesion to steel plate	1.6 N/cm	14.6 oz/in	AFERA 5001/PSTC 101

\*Typical value

All technical data provided is based on laboratory testing and is believed to be accurate. End users are responsible for determining product suitability for their intended application.

#### Technical Information and Product Use

All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. Figures shown refer to average values only, based on tests carried out in conditioned laboratory and are not valid for specification. The company reserves the right to modify or change the products at any time without notice. The accuracy or completeness of such information is not guaranteed. The technical information, suggestions and other statements contained in this document have been compiled for your guidance and usage. ATLAS Tapes Group reminds the user of the products to make sure that the product is used as per the instructions and suggestions provided. It is the user's sole responsibility to determine the suitability of the product in actual application under specific conditions.

#### Storage and Shelf Life

Suggested storage in dry area away from direct sunlight temperature should range from 59°F / 15°C to 77°F / 25°C with max relative humidity of 50%. Tape and jumbo roll should be used respectively within 12 months and 6 months from date of shipment. ATLAS Tapes Group does not take responsibility for the defective material if it is not stored and used in accordance with the conditions listed above.