

TECHNICAL DATA SHEET

Date of Issue 03/2026 | Rev. 00_03/2026

9340 Blue Painter's Performance Pro Painter's Masking Tape



PRODUCT DESCRIPTION

9340 Performance is a professional blue masking tape designed for precise indoor painting and decorative applications. Featuring a saturated crepe paper backing and acrylic adhesive, it provides reliable adhesion and clean removal without residue after application, without leaving residue. Its smooth release and consistent tack allow accurate masking on walls, trims, and other delicate surfaces. Resistant to UV light for short exposures, it maintains stable performance in mild temperature and humidity conditions. FSC® certified paper ensures sustainability and environmental care.



FEATURES

- Acrylic adhesive
- Clean removal without residue
- UV-resistant for short exposures
- Smooth unwind and precise edge definition
- Suitable for delicate indoor surfaces
- FSC® certified paper backing

MAIN APPLICATIONS

- Indoor painting and decoration
- Wall and trim masking
- Multi-coat decorative systems
- Precision masking for clean lines
- Suitable for Spray Painting

CONSTRUCTION

	Adhesive	Backing
Material	Water Based Acrylic	Saturated crepe paper
Colour	 Transparent	 Sea Blue

TECHNICAL DATA*

	Metric	Imperial Units	Test Method
Total weight	95 g/m ²	2.80 oz/yd ²	ISO 536
Total thickness	120 µm	4.7 mils	Internal
MD tensile strength	38 N/cm	21.7 lb/in	AFERA 5004/PSTC 131
MD elongation at break	11 %	11 %	AFERA 5004/PSTC 131
Adhesion to steel plate	1.2 N/cm	11 oz/in	AFERA 5001/PSTC 101

*Typical value

All technical data provided is based on laboratory testing and is believed to be accurate. End users are responsible for determining product suitability for their intended application.

Technical Information and Product Use

All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. Figures shown refer to average values only, based on tests carried out in conditioned laboratory and are not valid for specification. The company reserves the right to modify or change the products at any time without notice. The accuracy or completeness of such information is not guaranteed. The technical information, suggestions and other statements contained in this document have been compiled for your guidance and usage. ATLAS Tapes Group reminds the user of the products to make sure that the product is used as per the instructions and suggestions provided. It is the user's sole responsibility to determine the suitability of the product in actual application under specific conditions.

Storage and Shelf Life

Suggested storage in dry area away from direct sunlight temperature should range from 59°F / 15°C to 77°F / 25°C with max relative humidity of 50%. Tape and jumbo roll should be used respectively within 12 months and 6 months from date of shipment. ATLAS Tapes Group does not take responsibility for the defective material if it is not stored and used in accordance with the conditions listed above.