

TECHNICAL DATA SHEET

Date of Issue 03/2026 | Rev. 00_03/2026

9350 High Grade WR Color Body Shop Masking Tape



PRODUCT DESCRIPTION

9350 High Grade WR Color is a professional water-resistant masking tape designed for automotive refinishing and detailing. Built with a saturated crepe paper backing and natural rubber adhesive, it provides excellent adhesion and holding power even under humid or slightly wet conditions. Suitable for drying cycles up to 80°C, it guarantees clean removal and consistent edge definition. The tape maintains flexibility for curved or irregular surfaces and is ideal for use with both water and solvent base paints.

FSC® certified paper ensures a sustainable and responsible choice for professional body shops.

FEATURES

- Water resistant
- Temperature resistance up to 80°C (176°F)
- Excellent adhesion and holding power
- Clean removal and sharp paint edges
- Flexible and conformable
- FSC® certified paper backing

MAIN APPLICATIONS

- Automotive refinishing and detailing
- Wet sanding and humid environments
- Drying cycles up to 80°C
- Water-based paint applications

CONSTRUCTION

	Adhesive	Backing
Material	Natural rubber	Saturated crepe paper
Colour	Transparent	<input type="radio"/> Brown <input type="radio"/> Star Yellow <input checked="" type="radio"/> Green <input type="radio"/> Orange

TECHNICAL DATA*

	Metric	Imperial Units	Test Method
Total weight	95 g/m ²	2.80 oz/yd ²	ISO 536
Total thickness	125 µm	4.9 mils	Internal
MD tensile strength	38 N/cm	21.7 lb/in	AFERA 5004/PSTC 131
MD elongation at break	9 %	9 %	AFERA 5004/PSTC 131
Adhesion to steel plate	2 N/cm	18.3 oz/in	AFERA 5001/PSTC 101
Temperature resistance	80°C (1 hour)	176°F (1 hour)	

*Typical value

All technical data provided is based on laboratory testing and is believed to be accurate. End users are responsible for determining product suitability for their intended application.

Technical Information and Product Use

All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. Figures shown refer to average values only, based on tests carried out in conditioned laboratory and are not valid for specification. The company reserves the right to modify or change the products at any time without notice. The accuracy or completeness of such information is not guaranteed. The technical information, suggestions and other statements contained in this document have been compiled for your guidance and usage. ATLAS Tapes Group reminds the user of the products to make sure that the product is used as per the instructions and suggestions provided. It is the user's sole responsibility to determine the suitability of the product in actual application under specific conditions.

Storage and Shelf Life

Suggested storage in dry area away from direct sunlight temperature should range from 59°F / 15°C to 77°F / 25°C with max relative humidity of 50%. Tape and jumbo roll should be used respectively within 12 months and 6 months from date of shipment. ATLAS Tapes Group does not take responsibility for the defective material if it is not stored and used in accordance with the conditions listed above.