

## TECHNICAL DATA SHEET

Date of Issue 03/2026 | Rev. 00\_03/2026

# 9400 Superior WR Color Pro Painter's Masking Tape



## PRODUCT DESCRIPTION

9400 Superior WR Color is a premium all-weather masking tape engineered for professional indoor and outdoor painting. Combining a saturated crepe paper backing with a natural rubber adhesive, it offers outstanding adhesion, flexibility, and clean removal even in temperature extremes from -15°C to +40°C. The colored backing improves visibility and control during multi-stage masking operations. Water-resistant and UV-stable for short-term exposure, it ensures reliable performance on walls, metal, wood, and outdoor surfaces. FSC® certified paper guarantees environmental responsibility and consistent quality.




## FEATURES

- Water resistant
- Usable from -15°C to +40°C (5°F–104°F)
- Excellent adhesion on indoor/outdoor surfaces
- Clean removal without residue
- Colored backing for visibility
- FSC® certified paper backing

## MAIN APPLICATIONS

- Indoor and outdoor painting and decoration
- Exterior decoration and UV-exposed areas
- Multi-stage professional jobs
- Temperature-variable environments
- Suitable for Spray Painting

## CONSTRUCTION

	Adhesive	Backing
Material	Natural rubber	Saturated crepe paper
Colour	 Transparent	 Green  Orange

## TECHNICAL DATA\*

	Metric	Imperial Units	Test Method
Total weight	100 g/m <sup>2</sup>	2.95 oz/yd <sup>2</sup>	ISO 536
Total thickness	135 µm	5.3 mils	Internal
MD tensile strength	44 N/cm	25.1 lb/in	AFERA 5004/PSTC 131
MD elongation at break	5 %	5 %	AFERA 5004/PSTC 131
Adhesion to steel plate	2 N/cm	18.3 oz/in	AFERA 5001/PSTC 101
Temperature resistance	-15 ÷ + 40°C	5 ÷ + 104°F	

\*Typical value

All technical data provided is based on laboratory testing and is believed to be accurate. End users are responsible for determining product suitability for their intended application.

### Technical Information and Product Use

All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. Figures shown refer to average values only, based on tests carried out in conditioned laboratory and are not valid for specification. The company reserves the right to modify or change the products at any time without notice. The accuracy or completeness of such information is not guaranteed. The technical information, suggestions and other statements contained in this document have been compiled for your guidance and usage. ATLAS Tapes Group reminds the user of the products to make sure that the product is used as per the instructions and suggestions provided. It is the user's sole responsibility to determine the suitability of the product in actual application under specific conditions.

### Storage and Shelf Life

Suggested storage in dry area away from direct sunlight temperature should range from 59°F / 15°C to 77°F / 25°C with max relative humidity of 50%. Tape and jumbo roll should be used respectively within 12 months and 6 months from date of shipment. ATLAS Tapes Group does not take responsibility for the defective material if it is not stored and used in accordance with the conditions listed above.