

## TECHNICAL DATA SHEET

Date of Issue 03/2026 | Rev. 00\_03/2026

# 9435 Premium WR Color Pro Painter's Masking Tape



### PRODUCT DESCRIPTION

9435 Premium WR Color is a professional water-resistant masking tape designed for high-quality decorative and painting applications. Its saturated crepe paper backing and natural rubber adhesive ensure reliable adhesion and clean removal even under humid or demanding conditions. The colored backing enhances visibility during application, improving precision and workflow efficiency. Ideal for both indoor and outdoor decorative use, it provides sharp paint edges and consistent performance with water-based and solvent-based coatings. FSC® certified paper makes it an environmentally responsible choice for professional painters.

### FEATURES

- Water-resistant natural rubber adhesive
- Clean removal without residue
- Sharp paint edges
- Colored backing for better visibility
- Reliable adhesion on smooth and semi-textured surfaces
- FSC® certified paper backing

### MAIN APPLICATIONS

- Professional decorative and painting work
- Wet sanding and humid environments
- Colored masking for precision work
- Suitable for Spray Painting

### CONSTRUCTION

	Adhesive	Backing
Material	Natural rubber	Saturated crepe paper
Colour	Transparent	Star Yellow              Apricot              Sea Blue

### TECHNICAL DATA\*

	Metric	Imperial Units	Test Method
Total weight	95 g/m <sup>2</sup>	2.80 oz/yd <sup>2</sup>	ISO 536
Total thickness	125 µm	4.9 mils	Internal
MD tensile strength	38 N/cm	21.7 lb/in	AFERA 5004/PSTC 131
MD elongation at break	10 %	10 %	AFERA 5004/PSTC 131
Adhesion to steel plate	2 N/cm	18.3 oz/in	AFERA 5001/PSTC 101
Temperature resistance	80°C (30 min)	176°F (30 min)	

\*Typical value

All technical data provided is based on laboratory testing and is believed to be accurate. End users are responsible for determining product suitability for their intended application.

#### Technical Information and Product Use

All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. Figures shown refer to average values only, based on tests carried out in conditioned laboratory and are not valid for specification. The company reserves the right to modify or change the products at any time without notice. The accuracy or completeness of such information is not guaranteed. The technical information, suggestions and other statements contained in this document have been compiled for your guidance and usage. ATLAS Tapes Group reminds the user of the products to make sure that the product is used as per the instructions and suggestions provided. It is the user's sole responsibility to determine the suitability of the product in actual application under specific conditions.

#### Storage and Shelf Life

Suggested storage in dry area away from direct sunlight temperature should range from 59°F / 15°C to 77°F / 25°C with max relative humidity of 50%. Tape and jumbo roll should be used respectively within 12 months and 6 months from date of shipment. ATLAS Tapes Group does not take responsibility for the defective material if it is not stored and used in accordance with the conditions listed above.