TECHNICAL DATA SHEET

Date of Issue 03/2026 | Rev. 01_04/2026

PTHM440
Medium-Heavy Weight
Paper Packaging Tape ECO LINE

FSC
www.fsc.org
FSC®C173160
The mark of responsible forestry

INGEDE
Recycling-friendly tape according to INGEDE Method 12

PRODUCT DESCRIPTION

PTHM440 is a flatback crepe paper packaging tape with more than 80% bio-based reinforced for stability and controlled elongation, coated with a synthetic rubber adhesive that ensures very high adhesion and reliable instant tack. Its strong paper structure combined with outstanding holding power makes it suitable for light and medium-weight carton sealing, bundling, splicing and industrial packaging operations.
FSC® certified flatback paper supports sustainable packaging systems.

FEATURES

- Strong flatback crepe paper
- Very high adhesion
- Immediate tack
- Controlled elongation
- FSC® certified paper
- >80% bio-based paper
- Excellent holding power

MAIN APPLICATIONS

- Medium/light carton sealing
- Packaging & industrial use
- Splicing & bundling
- Paper-based packaging

CONSTRUCTION

	Adhesive	Backing
Material	Synthetic Rubber	>80% bio-based flatback paper
Colour	Transparent	Brown

TECHNICAL DATA*

	Metric	Imperial Units	Test Method
Film thickness	95 µm	3.7 mils	Internal
Adhesive weight	34 g/m²	1.00 oz/yd²	ISO 536
Total thickness	120 µm	4.7 mils	Internal
MD tensile strength	78 N/cm	44.5 lb/in	AFERA 5004/PSTC 131
MD elongation at break	3 %	3 %	AFERA 5004/PSTC 131
Adhesion to steel plate	11 N/cm	100.5 oz/in	AFERA 5001/PSTC 101

*Typical value

All technical data provided is based on laboratory testing and is believed to be accurate. End users are responsible for determining product suitability for their intended application.

Technical Information and Product Use

All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. Figures shown refer to average values only, based on tests carried out in conditioned laboratory and are not valid for specification. The company reserves the right to modify or change the products at any time without notice. The accuracy or completeness of such information is not guaranteed. The technical information, suggestions and other statements contained in this document have been compiled for your guidance and usage. ATLAS Tapes Group reminds the user of the products to make sure that the product is used as per the instructions and suggestions provided. It is the user's sole responsibility to determine the suitability of the product in actual application under specific conditions.

Storage and Shelf Life

Suggested storage in dry area away from direct sunlight temperature should range from 59°F / 15°C to 77°F / 25°C with max relative humidity of 50%. Tape and jumbo roll should be used respectively within 12 months and 6 months from date of shipment. ATLAS Tapes Group does not take responsibility for the defective material if is not stored and used in accordance with the conditions listed above.