

TECHNICAL DATA SHEET

Date of Issue 03/2026 | Rev. 01_07/2026

5350 Professional Washi Painter's Masking Tape



PRODUCT DESCRIPTION

5350 Professional is a professional washi masking tape designed for decorative painting and finishing. Made with high-quality Japanese washi paper and acrylic adhesive, it guarantees clean removal and sharp paint edges without leaving residue. Its balanced tack and excellent conformability ensure reliable performance on walls, wood, and metal, even during medium-length painting cycles. Water resistant and UV resistant for up to 60 days, it combines precision, versatility, and sustainability thanks to its FSC® certified paper backing.

FEATURES

- Japanese washi paper backing
- Acrylic adhesive
- Water resistant
- UV resistant (60 days)
- Clean removal without residue
- Sharp and defined paint edges
- FSC® certified paper backing

MAIN APPLICATIONS

- Professional decorative painting and finishing
- Precision masking on smooth and semi-textured surfaces
- Multi-color painting and detailing
- Water-based and solvent-based paint systems
- Suitable for Spray Painting

CONSTRUCTION

	Adhesive	Backing
Material	Water Based Acrylic	Washi paper
Colour	 Transparent	 Orange

TECHNICAL DATA*

	Metric	Imperial Units	Test Method
Total weight	75 g/m ²	2.21 oz/yd ²	ISO 536
Total thickness	90 µm	3.5 mils	Internal
MD tensile strength	22 N/cm	12.6 lb/in	AFERA 5004/PSTC 131
MD elongation at break	3 %	3 %	AFERA 5004/PSTC 131
Adhesion to steel plate	1.6 N/cm	14.6 oz/in	AFERA 5001/PSTC 101

*Typical value

All technical data provided is based on laboratory testing and is believed to be accurate. End users are responsible for determining product suitability for their intended application.

Technical Information and Product Use

All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. Figures shown refer to average values only, based on tests carried out in conditioned laboratory and are not valid for specification. The company reserves the right to modify or change the products at any time without notice. The accuracy or completeness of such information is not guaranteed. The technical information, suggestions and other statements contained in this document have been compiled for your guidance and usage. ATLAS Tapes Group reminds the user of the products to make sure that the product is used as per the instructions and suggestions provided. It is the user's sole responsibility to determine the suitability of the product in actual application under specific conditions.

Storage and Shelf Life

Suggested storage in dry area away from direct sunlight temperature should range from 59°F / 15°C to 77°F / 25°C with max relative humidity of 50%. Tape and jumbo roll should be used respectively within 12 months and 6 months from date of shipment. ATLAS Tapes Group does not take responsibility for the defective material if it is not stored and used in accordance with the conditions listed above.